

# DECLARATION OF PERFORMANCE

pursuant to Annex III of Regulation (EU) No. 305/2011  
No. DU200 - CPR - 2025 Rev A

1. Unique identification code of the product type: **Skye E700 Store Stand, Roomheaters for solid fuel**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Space Heating in Residential Buildings (without water heating)**
3. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):  
**Charnwood, A.J.Wells & Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS, UK, Phone +44 (0) 1983 537770**
4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): - **N/A**
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **3**
6. The RRF notified test laboratory, identification number 1625, performed the initial test and inspection under System 3 and documented it in test report 1021 24 1070
7. Declared performance:

Harmonised technical specification	EN16510-1:2022 EN16510-2-1																																																	
Essential characteristics																																																		
<b>Mechanical strength and stability</b>																																																		
Chimney Load Capacity	120 kg																																																	
<b>Fire protection</b>																																																		
Protection of flammable materials; minimum distance to combustibles Distance under the fireplace $d_B$ Distance from the floor to the front $d_F$ Distance to ceiling $d_C$ Distance to rear wall $d_R$ Distance to side wall $d_S$ Distance to the side wall in the radiation area $d_L$ Minimum distance to neighbouring flammable materials (e.g. furniture) $d_P$ Material type and material thickness of the thermal insulation $s$																																																		
NPD - No Performance Determined	<table border="1"> <thead> <tr> <th></th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>safety test configuration</td> <td>1</td> <td>1</td> <td>NPD</td> </tr> <tr> <td><math>d_B</math> (mm)</td> <td>0</td> <td>0</td> <td>NPD</td> </tr> <tr> <td><math>d_F</math> (mm)</td> <td>560</td> <td>600</td> <td>NPD</td> </tr> <tr> <td><math>d_C</math> (mm)</td> <td>750</td> <td>750</td> <td>NPD</td> </tr> <tr> <td><math>d_R</math> (mm)</td> <td>250</td> <td>100</td> <td>NPD</td> </tr> <tr> <td><math>d_S</math> (mm)</td> <td>300</td> <td>350</td> <td>NPD</td> </tr> <tr> <td><math>d_L</math> (mm)</td> <td>NPD</td> <td>0</td> <td>NPD</td> </tr> <tr> <td><math>d_P</math> (mm)</td> <td>1100</td> <td>1000</td> <td>NPD</td> </tr> <tr> <td><math>s</math></td> <td>0 0 0 0</td> <td>0 0 0 0</td> <td>NPD</td> </tr> <tr> <td>Insulated flue</td> <td>X</td> <td>✓</td> <td>NPD</td> </tr> <tr> <td>Heatshield (optional)</td> <td>X</td> <td>✓</td> <td>NPD</td> </tr> </tbody> </table>			1	2	3	safety test configuration	1	1	NPD	$d_B$ (mm)	0	0	NPD	$d_F$ (mm)	560	600	NPD	$d_C$ (mm)	750	750	NPD	$d_R$ (mm)	250	100	NPD	$d_S$ (mm)	300	350	NPD	$d_L$ (mm)	NPD	0	NPD	$d_P$ (mm)	1100	1000	NPD	$s$	0 0 0 0	0 0 0 0	NPD	Insulated flue	X	✓	NPD	Heatshield (optional)	X	✓	NPD
	1	2	3																																															
safety test configuration	1	1	NPD																																															
$d_B$ (mm)	0	0	NPD																																															
$d_F$ (mm)	560	600	NPD																																															
$d_C$ (mm)	750	750	NPD																																															
$d_R$ (mm)	250	100	NPD																																															
$d_S$ (mm)	300	350	NPD																																															
$d_L$ (mm)	NPD	0	NPD																																															
$d_P$ (mm)	1100	1000	NPD																																															
$s$	0 0 0 0	0 0 0 0	NPD																																															
Insulated flue	X	✓	NPD																																															
Heatshield (optional)	X	✓	NPD																																															
<b>Hygiene, health and environmental protection</b>																																																		
Emissions (Threshold values) Carbon monoxide emission (CO) Nitrogen emission (NO <sub>x</sub> ) Emission of organic gaseous carbon (OGC) Dust emissions (PM)	<table border="1"> <thead> <tr> <th></th> <th>At nominal heat output</th> <th>With partial load heat output</th> </tr> </thead> <tbody> <tr> <td>CO</td> <td>1500</td> <td>NPD</td> </tr> <tr> <td>NO<sub>x</sub></td> <td>200</td> <td>NPD</td> </tr> <tr> <td>OGC</td> <td>120</td> <td>NPD</td> </tr> <tr> <td>PM</td> <td>40</td> <td>NPD</td> </tr> </tbody> </table>			At nominal heat output	With partial load heat output	CO	1500	NPD	NO <sub>x</sub>	200	NPD	OGC	120	NPD	PM	40	NPD																																	
	At nominal heat output	With partial load heat output																																																
CO	1500	NPD																																																
NO <sub>x</sub>	200	NPD																																																
OGC	120	NPD																																																
PM	40	NPD																																																
<b>Safety and accessibility during use</b>																																																		
Data for installation on a chimney Flue gas outlet temp. $T_{snom}$ Minimum flue draught $P_{snom}$ Flue gas mass flow rate $\phi_{snom}$	<table border="1"> <thead> <tr> <th>Fuel 1</th> <th>At nominal heat output</th> <th>With partial load heat output</th> <th>Fuel 2</th> <th>At nominal heat output</th> </tr> </thead> <tbody> <tr> <td><math>T_{snom}</math></td> <td>211</td> <td>NPD</td> <td><math>T_{snom}</math></td> <td>NPD</td> </tr> <tr> <td><math>P_{snom}</math></td> <td>12</td> <td>NPD</td> <td><math>P_{snom}</math></td> <td>NPD</td> </tr> <tr> <td><math>\phi_{snom}</math></td> <td>4.7</td> <td>NPD</td> <td><math>\phi_{snom}</math></td> <td>NPD</td> </tr> </tbody> </table>		Fuel 1	At nominal heat output	With partial load heat output	Fuel 2	At nominal heat output	$T_{snom}$	211	NPD	$T_{snom}$	NPD	$P_{snom}$	12	NPD	$P_{snom}$	NPD	$\phi_{snom}$	4.7	NPD	$\phi_{snom}$	NPD																												
Fuel 1	At nominal heat output	With partial load heat output	Fuel 2	At nominal heat output																																														
$T_{snom}$	211	NPD	$T_{snom}$	NPD																																														
$P_{snom}$	12	NPD	$P_{snom}$	NPD																																														
$\phi_{snom}$	4.7	NPD	$\phi_{snom}$	NPD																																														
<b>Data for installation on a chimney with regard to fire safety</b>																																																		
Fire safety for installation on the chimney	T400 - G																																																	
<b>Energy saving and thermal insulation</b>																																																		
Heat output and energy efficiency of the appliance Room heating output $P_{shnom}$ Water heat output $P_{Nnom}$ Efficiency $\eta_{nom}$	<table border="1"> <thead> <tr> <th>Fuel 1</th> <th>At nominal heat output</th> <th>With partial load heat output</th> <th>Fuel 2</th> <th>At nominal heat output</th> </tr> </thead> <tbody> <tr> <td><math>P_{shnom}</math></td> <td>7.4</td> <td>NPD</td> <td><math>P_{shnom}</math></td> <td>NPD</td> </tr> <tr> <td><math>P_{Nnom}</math></td> <td>NPD</td> <td>NPD</td> <td><math>P_{Nnom}</math></td> <td>NPD</td> </tr> <tr> <td><math>\eta_{nom}</math></td> <td>89</td> <td>NPD</td> <td><math>\eta_{nom}</math></td> <td>NPD</td> </tr> </tbody> </table>		Fuel 1	At nominal heat output	With partial load heat output	Fuel 2	At nominal heat output	$P_{shnom}$	7.4	NPD	$P_{shnom}$	NPD	$P_{Nnom}$	NPD	NPD	$P_{Nnom}$	NPD	$\eta_{nom}$	89	NPD	$\eta_{nom}$	NPD																												
Fuel 1	At nominal heat output	With partial load heat output	Fuel 2	At nominal heat output																																														
$P_{shnom}$	7.4	NPD	$P_{shnom}$	NPD																																														
$P_{Nnom}$	NPD	NPD	$P_{Nnom}$	NPD																																														
$\eta_{nom}$	89	NPD	$\eta_{nom}$	NPD																																														
<b>Room heating efficiency</b>																																																		
Seasonal space heating energy efficiency (at nominal heat output)	79																																																	
Energy efficiency (EEI)	119																																																	
Energy efficiency class	A+																																																	
Power consumption at nominal heat output $e_{l,max}$	0.004																																																	
Power consumption at partial load heat output	NPD																																																	
Power consumption in standby mode $e_{l,SB}$	0.004																																																	
<b>Sustainable use of natural resources</b>																																																		
Ecological sustainability	NPD																																																	

8. The performance of the above-mentioned product corresponds to the declared performance(s).

Only the manufacturer named above is responsible for generating the declaration of performance in accordance with EU regulation No. 305/2011.

Signed for and on behalf of the manufacturer by:

Paul Wells, Technical Director, Newport, Isle of Wight, 5.11.2025